

# HD 13 VT

Tandem roller with vibrating roller drum and set of tyres

Tandem rollers Series HD CompactLine / Series H201



## HIGHLIGHTS HD CompactLine

- > Simple, intuitive and language-neutral operation
- > Easy transport, simple loading
- > Ergonomic driver platform
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Compact dimensions

Machine dimensions		
Total length (L)	mm	2896
Width (B)	mm	1426
Total height (H)	mm	2590
Drum width (X)	mm	1300
Height loading, min. (Hl)	mm	1820



TECHNICAL DATA		Unit	HD 13 VT
	<b>Weights</b>		
	Operating weight with ROPS	kg	3825
	Operating weight, max.	kg	4790
	Static linear load, front	kg/cm	15,5
	French classific., data/class		10,5/VT0
	<b>Machine dimensions</b>		
	Total length	mm	2896
	Total height with cab	mm	2720
	Total height with ROPS	mm	2590
	Height loading, min.	mm	1820
	Wheel base	mm	1950
	Total width	mm	1426
	Max. working width	mm	1338
	Kerb clearance, left/right	mm	720/720
	Turning radius, inside	mm	2690
	<b>Drum dimensions</b>		
	Drum width, front	mm	1300
	Drum diameter, front	mm	900
	Drum thickness, front	mm	17
	Drum type, front		Smooth/non-split
	Track offset, left/right	mm	0/50
	<b>Wheel dimensions</b>		
	Size of tyres, rear		10,5/80-16
	Width over tyres, rear	mm	1276
	Number of tyres, rear		4
	<b>Diesel engine</b>		
	Manufacturer		KUBOTA
	Version		V2203
	Number of cylinders		4
	Power rat. ISO 14396, kW/PS/rpm		34,6/47,1/2700
	Power rating SAE J1349, kW/HP/rpm		34,6/46,4/2700
	Emission standard		EU Stage IIIA
	Exhaust gas after-treatment		-
	<b>Drive</b>		
	Speed, infinitely variable	km/h	0 - 11,0
	Climbing ability, vibration on/off	%	30/40
	<b>Vibration</b>		
	Vibration frequency, front, I/II	Hz	60/51
	Amplitude, front, I/II	mm	0,51/0,31
	Centrifugal force, front, I/II	kN	64/39
	<b>Steering</b>		
	Oscillation angle +/-	°	8
	Steering, type		Articulated steering
	<b>Sprinkler system</b>		
	Water sprinkler, type		Pressure
	<b>Tank capacity/Fill capacity</b>		
	Fuel tank, capacity	L	73
	Water tank, capacity	L	260
	Additive tank, capacity	L	18
	<b>Sound level</b>		
	Acoustic power LW(A), sticker		106
	Acoustic power LW(A), measured		102

#### EQUIPMENT

3-point articulation, Dashboard with displays, indicator lights and switches, Dashboard cover, lockable and weather-resistant, Handrails, Pressure water sprinkling with interval switch, Operator's platform with entry from both sides, Hydrostatic steering, Vibration-isolated operator's platform, Track offset

#### OPTIONAL EQUIPMENT

Plastic scraper, foldable, ROPS, foldable, Edge pressing and cutting equipment, Chip spreader, Anti-freeze injection system, Automatic engine-off function, Back-up alarm (reversing), Working lights, Rotating beacon, Drum edge lighting, Water drain valve, Tow eye, at the front, Tow hitch, V-belt protection

**HAMM AG**  
Hammstraße 1  
D-95643 Tirschenreuth  
Tel +49 9631 80-0  
Fax +49 9631 80-111  
www.hamm.eu

